



富捷科技

Product Datasheet

产品规格说明书

FWKP Series

High Power Low TCR Four-pin Alloy Chip Resistors

**FWKP 系列高功率低温
漂四引脚合金贴片电阻**

安徽省富捷电子科技有限公司

ANHUI FOJAN ELECTRONICS TECHNOLOGY CO., LTD


安徽省马鞍山市郑蒲港新区金蒲电子产业园

JINPU ELECTRONIC INDUSTRIAL PARK, ZHENGPU PORT NEW
DISTRICT, MAANSHAN CITY, ANHUI PROVINCE

zoey@fosan.net.cn www.fosan.vip

FWKP 系列高功率低温漂四引脚合金贴片电阻

High Power Low TCR Four-pin Alloy Chip Resistors FWKP Series



■ 特点 (Features)

- 电子束焊接工艺
- 耐冲击
- 用于电流检测的低电流，高精度电阻
- 低电感
- 四引脚开尔文结构
- 低温度系数（可达 $\pm 20\text{ppm}/^\circ\text{C}$ ）
- 符合 AEC-Q200 可靠性测试
- 无铅，符合 RoHS、Reach 要求
- 特殊规格可定制
- Electron beam welding process
- Ideal for pulse application
- Low Resistance and High Accuracy Resistor for Current Detection
- Low inductance
- Four-pin Kelvin structure
- Low TCR (Up to $\pm 20\text{ppm}/^\circ\text{C}$)
- Complies with AEC-Q200 reliability test
- Pb-free to Meet RoHS 、Reach Requirements
- Special specifications can be customized

■ 应用 (Application)

- 电池化成分容系统
- 仪器电源及电源测试系统
- 自动化控制电源
- 变频驱动与伺服驱动系统
- 电池内阻检测设备
- 精密采样的电源系统
- Batterized component volume system
- Instrument power supply and power test system
- Automation Control Power Supply
- Variable frequency drives and servo drive systems
- Battery internal resistance detection equipment
- Power systems that require precision sampling

■ 产品料号 (Parts Number Explanation) 示例：FWKP27265WFR001RK

FWKP 系列	2726 型别	5W 功率	F 公差	R001 字码	R 包装别	K 材质	特殊型
FOSAN Type	2726 4026	5W:5W 3W:3W	D: $\pm 0.5\%$ F: $\pm 1\%$ G: $\pm 2\%$ J: $\pm 5\%$	R001=1m Ω 0M50=0.5m Ω	T: 7 inch reel R:13 inch reel B:Bulk	S: CuMnSn M: CuMn K: Karma	Blank: none
Type	Size	Power	Tolerance	Resistance	Packaging	Termination	Special

尺寸 (Dimension)

产品尺寸
Product
Dimension


(4026)

(2726)

单位 (unit) : mm

型别 (Size)	Resistance (mΩ)	Product Dimension					
		L	W	A	X	T	H
2726	0.2~5	6.9±0.3	6.6±0.3	2.0±0.2	4.8±0.4	0.9±0.1	3.0±0.5
4026	0.2~5	10.1±0.3	6.6±0.3	2.5±0.2	5.0±0.4	0.9±0.1	3.0±0.5

推荐焊盘尺寸 (Recommended Pad Dimension)

焊盘尺寸 Pad Dimension						
型别 (Size)	Resistance (mΩ)	Pad Dimension				
		a	c	e	f	g
2726	0.2~5	2.9	2.0	0.9	0.8	5.6
4026	0.2~5	4.0	5.5	0.9	0.8	5.6

单位 (unit) : mm



■ 电气特性 (Electrical characteristics)

型别 Type	阻值 Resistance (mΩ)	材质 Element Material	厚度 D± 0.15 (mm)	T.C.R. (PPM/°C)	额定功率 Power Rating at P70 (W)	精度 Tolerance (%)	使用温度 范围 Operating Temperature (°C)
2726	0.2	CuMnSn	0.40	±40	12	±0.5%、±1% ±2%、±5%	-55~170
	0.3	CuMn	0.40	±40	11		
	0.5		0.67	±40	9		
	0.6		0.57	±40	8		
	0.75		0.45	±40	7		
	0.9		0.37	±40	7		
	1		0.33	±40	7		
	1	Karma	0.40	±20	7		
	2		0.51	±20	6		
	3		0.34	±20	5		
	4		0.40	±20	4		
	5		0.40	±20	3		
4026	0.2	CuMnSn	0.40	±40	12		
	0.3	CuMn	0.40	±40	11		
	0.5		0.67	±40	9		
	0.6		0.57	±40	8		
	0.75		0.45	±40	7		
	0.9		0.37	±40	7		
	1		0.33	±40	7		
	1	Karma	0.40	±20	7		
	2		0.47	±20	6		
	3		0.34	±20	5		
	4		0.40	±20	4		
	5		0.40	±20	3		

如有非标准品的需求,请联系我们的业务部门 For non-standard parts, please contact our sales dept.

■ 印字标识 (Marking)

产品阻值使用两种方式表示:

- a. 以 “R” 字指示 Ω 的小数点的位置
- b. 以 “m” 字指示 mΩ 的小数点的位置

例:

R001 1%=1mΩ 1%;

0m50 1%=0.5mΩ 1%; 2m50 1%=2.5mΩ 1%

The resistance value of the product is expressed in two ways:

- a. The decimal point of Ω is indicated by the character "R".
- b. Using "m" to indicate the decimal point of mΩ.

E.g.,


R001 1%=1mΩ 1%;

0m50 1%=0.5mΩ 1%; 2m50 1%=2.5mΩ 1%

■ 性能 (Performance)


Test Items 测试项目	Reference 依据标准	Conditions of Test 测试条件	Test Limits 测试结果
Temperature Coefficient of Resistance 温度系数	AEC-Q200 TEST 19 IEC 60115-1 4.8	Measuring points -55°C and +120°C, reference point +20°C 测量点-55°C和+120°C, 参考点+20°C	见图表
High Temperature Exposure (Storage) 高温存储	AEC-Q200-REV D-Test 3 MIL-STD202 Method 108	T=170°C,1000hrs, Measurement at 24hrs after test conclusion. 170°C, 1000 小时, 测试结束后 24 小时测量。	$\Delta R \leq \pm 1\%$
Temperature Cycling 温度循环	AEC-Q200-REV D-Test 4 JESD22 Method JA-104	1000 Cycle (-55°C to 125°C) Measurement at 24hrs after test conclusion. 1000 次循环 (-55°C至 125°C) 测试结束后 24 小时进行测量。	$\Delta R \leq \pm 0.5\%$
Short time overload 短时过载	IEC60115-1 4.13	5 X rated power for 5s 5 倍额定功率,5 秒	$\Delta R \leq \pm 0.5\%$
Biased Humidity 高温高湿	AEC-Q200-REV D-Test 7 MIL-STD-202 Method 103	10% Rated power at 85°C, RH:85%, 1000Hrs,Measurement at 24hrs after test conclusion. 10%额定功率, 85°C, 相对湿度: 85%, 1000 小时, 测试结束后 24 小 时测量。	$\Delta R \leq \pm 0.5\%$
Load Life 负载寿命	AEC-Q200-REV D-Test 8 MIL-STD-202 Method 108	1000 h at +70 °C, 1.5 h "ON", 0.5 h "OFF", Measurement at 24hrs after test conclusion. 1000 小时, +70 °C, 1.5 小时"开启", 0.5 小时"关闭", 测试结束后 24 小时测量。	$\Delta R \leq \pm 1\%$
Resistance to Soldering Heat 耐焊接热	AEC-Q200-REV D-Test 15 MIL-STD-202 Method 210	T=260±5°C solder,10±1 sec dwell 260±5°C焊接, 停留 10±1 秒。	$\Delta R \leq \pm 0.5\%$
Mechanical Shock 机械冲击	AEC-Q200-REV D-Test 13 MIL-STD-202 Method 213	100g's, Normal duration is 6ms, half sine shock pulse 正弦半波,峰值加速度 100g's,脉冲持续 6ms,三轴六向各 3 次。	$\Delta R \leq \pm 0.5\%$
Thermal Shock 冷热冲击	AEC-Q200-REV D-Test 16 MIL-STD-202 Method 107	-55°C/+155°C. Note: Number of cycles required-1000, Maximum transfer time-20 seconds, Dwell time-15 minutes. -55°C,15 分钟~常温<20 秒~+155°C,15 分钟,1000 个循环	$\Delta R \leq \pm 1\%$
Solderability 可焊性	AEC-Q200-REV D-Test 18 J-STD-002	Dip the terminal in a flux and then dip into a soldering bath at 245± 5°C for 3±0.5sec 沾助焊剂后浸入锡炉, 锡炉温度 245±5°C, 时间 3±0.5 秒。	> 95% area covered > 95%面积上锡

■ 功率衰减曲线 (Derating Curve)




■ 焊接 (soldering)

- 建议回流焊曲线 (Recommend reflow soldering profile)



- 建议波峰焊曲线 (Recommend wave soldering profile)



- 手工焊温度 (hand soldering temperature)


烙铁温度 $350 \pm 10^\circ\text{C}$ 3 秒之内, 避免烙铁接触电阻本体

The iron temperature is $350 \pm 10^\circ\text{C}$, hand soldering time less than 3S. Avoid solder iron tip direct touch the components body


■ 包装规格 (Tapping Specification)

- 卷盘尺寸 (Reel dimension)

Type	Size		Unit	φA	φB	φC	F	W
2726	13"	1K/Reel	mm	330±2.0	100±1.0	13.5±1.0	21.0±2.0	16.5±0.2
4026	13"	1K/Reel	mm	330±2.0	100±1.0	13.5±1.0	29.0±2.0	24.5±0.2



- 包装尺寸 (packing dimension)




Size	A±0.2	B±0.2	W±0.2	E±0.1	F±0.1	P0±0.1	P1±0.1	P2±0.1	φD0	T
2726	7.5	8.0	16	1.75	7.35	12.0	12	6.0	1.5	3.8
4026	7.5	12.1	24	1.75	12.2	12.0	12	6.0	1.5	3.8

■ 上胶带剥离力测试 (Peel force of top cover tape)

上胶带以 200mm/分钟的速度，沿 165~180 度角的方向进行剥离，如下图所示。纸带的剥离力范围为 10g~70g；载带的剥离力范围 30~100g。

The top cover tape is pulled at a speed of 200 mm/min with the angle between the tape during peel and the direction of unreeling maintained at 165 to 180 degree as following picture. The peel force of paper carrier tape shall be 0.1N to 0.7N(10 to 70 g), the peel force of plastic carrier tape shall be 0.3N to 1N (30 to 100 g)



■ 合金电阻器使用说明 (Alloy Resistor Instructions for use)

本产品以下特殊环境下应用，性能可能会受到影响：

(Application of the products in a special environment can deteriorate product performance) :

1. 高温；
High temperature
2. 有海风或腐蚀性气体，包括氯气，硫化氢，氨气，二氧化硫，二氧化氮等；
Near the sea, or corrosive gas, such as Cl_2 , H_2S , NH_3 , SO_2 and NO_2 etc;
3. 各种类型的液体，包括水，油，化学品，有机溶剂的使用；
Unverified liquids, such as water, oil, chemical or organic solvent;
4. 在用树脂或其他涂层材料密封产品的情况下使用；
Unverified resin or paint to cover products;
5. 焊接后使用不洁焊剂或使用水或水溶性清洁剂清洗产品
Products should be washed with soluble cleaner even if non cleaning flux.

■ 储存 / 搬运条件 (Storage / Carry conditions)

1. 储存温度 $25\pm5^{\circ}C$ Temperature: $25\pm5^{\circ}C$
2. 湿度 30~70%RH Humidity: 30~70%RH
3. 储存期限：先进先出，2 年 Storage life: 2years FIFO
4. 存放和搬运时，请保持盒子的正确方向。严禁跌落在箱体上，否则可能损坏产品电极或本体
Please hold box correct orientation when storing and carrying. It is strictly prohibited to fall on the box. otherwise the product electrode or body may be damaged.

■ 修订履历 (Revision History)

[illegible]