



富捷科技

Product Datasheet

产品规格说明书

FTR Series Automotive Anti-Sulfured Thin Film Chip Resistor

抗硫化车规薄膜片式电阻器

安徽省富捷电子科技有限公司

ANHUI FOJAN ELECTRONICS TECHNOLOGY CO., LTD

安徽省马鞍山市郑蒲港新区金蒲电子产业园

JINPU ELECTRONIC INDUSTRIAL PARK, ZHENGPU PORT NEW
DISTRICT, MAANSHAN CITY, ANHUI PROVINCE

zoey@fosan.net.cn www.fosan.vip

抗硫化车规薄膜片式电阻器 Automotive Grade Anti-sulfured Thin Film Chip Resistor FTR Series



特点 (Features)

- 电性能稳定, 可靠度高 - Stable electrical capability and high Reliability
- 符合 RoHS 指令要求 - Compliant with RoHS directive
- 符合无卤素要求 - Halogen free requirement
- 符合 汽车标准相关条款 - Compliant with AEC-Q200 standard
- 低温漂, 高精度 - High Precision and Low TCR
- 具有优越的抗硫化性能 - With excellent Anti-sulfured performance

应用 (Application)


- 广泛应用于汽车电子设备、工业设备、医疗设备、测试与测试设备、电信设备及消费类电子产品等领域。
- Widely used in Automotive electronics, Industrial, medical equipment, Test and measuring equipment and Telecommunications electronics etc.

产品料号 (Parts Number Explanation) 示例: FTR1206F1001TSX

F 公司	TR 产品别	1206 尺寸	F 公差	1001 字码	T 包装别	S 端电极	X 特殊码
FOJAN	TR: Automotive Anti-sulfured Thin film Others series refer to Catalogue	0402	A:±0.05%	±5%:E24	T: 7 inch reel	S: Sn	A:10ppm
		0603	B:±0.1%	3-digits+blank	Q:10 inch reel	C: Cu	E:15ppm
		0805	C:±0.25%	102=1KΩ	R:13 inch reel	A: Au	X:25ppm
		1206	D:±0.5%	1R0=1Ω	B:Bulk		V:50ppm
		1210	F:±1%	±1%&Below:			
		1218	J:±5%	E24+E96:			
		1812		4-digits			
		2010		1001=1KΩ			
		2512		1R00=1Ω			
Company	Type	Size	Tolerance	Resistance	Packaging	Termination	Special Case

■ 电阻结构 (Construction)


NO.	结构 Construction	主要材料 Major Material
1	陶瓷基板 Ceramic substrate	三氧化二铝 Al_2O_3
2	银电极 Conductive layer (Top)	银 Ag
3	银电极 Conductive layer (Top)	银 Ag
4	抗硫化层 Anti-sulfured layer	低温银 Ag
5	侧电极 Side conductive layer	镍铬合金 NiCr
6	阻体层 Resistive layer	合金 Alloy
7	内保护层 Inner protective layer	环氧树脂 Epoxy
8	外保护层 Outer Protective layer	环氧树脂 Epoxy
9	文字 Marking	镍 Ni
10	镍电极 Ni plating layer	锡 Sn
11	锡电极 Sn plating layer	银 Ag



■ 尺寸 (Dimension):

型别 (Type)		L	W	H	T1	T2
英制	公制					
0402	1005	1.00 ± 0.05	0.50 ± 0.05	0.35 ± 0.05	0.20 ± 0.10	0.25 ± 0.10
0603	1608	1.60 ± 0.10	0.80 ± 0.10	0.45 ± 0.10	0.25 ± 0.15	0.25 ± 0.15
0805	2012	2.00 ± 0.10	1.25 ± 0.10	0.50 ± 0.10	0.35 ± 0.20	0.40 ± 0.20
1206	3216	3.10 ± 0.10	1.60 ± 0.10	0.55 ± 0.10	0.45 ± 0.20	0.45 ± 0.20
1210	3225	3.10 ± 0.10	2.50 ± 0.15	0.55 ± 0.10	0.45 ± 0.15	0.50 ± 0.20
1218	3245	3.10 ± 0.10	4.60 ± 0.10	0.55 ± 0.10	0.45 ± 0.20	0.40 ± 0.20
1812	4532	4.50 ± 0.20	3.10 ± 0.20	0.55 ± 0.10	0.55 ± 0.20	0.70 ± 0.20
2010	5025	5.00 ± 0.10	2.50 ± 0.15	0.55 ± 0.10	0.45 ± 0.15	0.50 ± 0.20
2512	6432	6.35 ± 0.10	3.10 ± 0.15	0.55 ± 0.10	0.60 ± 0.20	0.90 ± 0.20

尺寸 Dimension



单位 (unit): mm

■ 温度系数 (Temperature Coefficient)

型别 Type	阻值范围 Resistance Range				T.C.R.(PPM/°C)
	B ±0.1%	C ±0.25%	D ±0.5%	F ±1%	
0402	10R~68K				±10
					±15
	4R7~220K		2R2~220K		±25
					±50
0603	10R~332K				±10
					±15
	4R7~680K		2R2~680K		±25
					±50
0805	10R~680K				±10
					±15
	4R7~1M0		2R2~1M0		±25
					±50
1206	10R~1M0				±10
					±15
	4R7~1M5		2R2~1M5		±25
					±50
1210	10R~1M0				±10
					±15
	4R7~1M0		2R2~1M0		±25
					±50
2010	10R~1M0				±10
					±15
	4R7~1M0		2R2~1M0		±25
					±50
2512	10R~1M0				±10
					±15
	4R7~1M0		2R2~1M0		±25
					±50

■ 电气特性 (Electrical characteristics)

型别 Type	70°C 下额定功率 Rated Power at 70°C	最大工作电压 Max Working Voltage	最大过负荷电压 Max Overload Voltage	绝缘耐压 Dielectric Withstanding Voltage
0402	1/16W	50V	100V	300V
0603	1/10W	75V	150V	300V
0805	1/8W	150V	300V	500V
1206	1/4W	200V	400V	500V
1210	1/2W	200V	400V	500V
1812	3/4W	200V	500V	500V
2010	3/4W	200V	400V	500V
2512	1W	200V	400V	500V

备注 (Remark): 额定电压计算公式 (The rated voltage is calculated by the following formula):

$$E = \sqrt{RP}$$

E: 额定电压 (Rated Voltage) (V)


P: 额定功率 (Rated Power) (W)

R: 电阻阻值 (Resistance) (ohm)

如果计算出的电压超过此型别的最大工作电压, 则此型别的最大工作电压为此电阻的额定电压。

In case the value calculated by the formula exceed the maximum working voltage as above table 8, the maximum working voltage shall be regarded as rated voltage.

■ 功率衰减曲线 (Derating Curve)

使用温度范围 Temperature usage range	-55°C~+155°C (其他)
说明 Describe	周围温度若超过 70°C 至 155°C 之间, 功率可照下图曲线予以修订 If the ambient temperature exceeds 70°C to 155°C, the power can be revised according to the curve in the following figure
功率衰减 曲线图 Power Attenuation Curve	 <p>The graph shows the power attenuation curve. The y-axis is 'Percent rated load (%)' ranging from 0 to 100. The x-axis is 'Ambient temperature (°C)' ranging from -55 to 160. The curve is constant at 100% for temperatures up to 70°C. From 70°C to 155°C, the load decreases linearly from 100% to 0%. There are dashed vertical lines at 70°C and 155°C, and arrows pointing left from the 100% mark on the y-axis.</p>

FTR 系列抗硫化车规薄膜片式电阻器规格书

性能 (Performance)

内容 Item	测试方法 Test Methods	测试条件 Test Conditions	规格 Specification
温度系数 Temperature Coefficient	JIS C 5201 4.8	TCR= $(R-R_0) / (t-t_0) R_0 \times 10^6$ (ppm) R0: 电阻在室温下的阻值 (resistance at room temperature) R: 电阻在 125°C或-55°C下的阻值 (resistance at 125°C or -55°C) t0: 室温 (room temperature) t:测试温度 (test temperature 125°C or -55°C)	As SEPC
短时间过负荷 Short-time overload	JIS C 5201 4.13	加载 2.5 倍的额定电压, 时间 5 秒后测量试验前后的阻值变化率。 Applied 2.5 times of rated voltage for 5 second. Measure the variation of resistance.	0.5%/1%: $\pm(1.0\%+0.05\Omega)$ 5%: $\pm(2.0\%+0.05\Omega)$
高温储存 High Temperature Exposure	AEC-Q200 TEST 3 MIL-STD-202 METHOD 108	125°C下放置 1000h, 不加载功率, 试验结束 24 \pm 4 小时后进行测试。 1000 hrs. @ T=155 . Un-powered. Measurement at 24 \pm 4 hours °C after test conclusion	$\pm(1.00\%+0.05\Omega)$
温度循环 Temperature Cycling	AEC-Q200 TEST 4 JESD22 METHOD JA-104	-55 ~ + 155 , °C °C 循环 1000 次, 在每一个极限温度持续时间不超过 30 分钟, 且温度转换时间不超过 1 分钟 , 试验结束 24 \pm 4 小时后进行测试。 1000 Cycles (-55 to +155) Measurement at 24 \pm 4 hours °C °C after test conclusion. 30min maximum dwell time at each temperature extreme. 1min. maximum transition time.	$\pm(2.00\% + 0.05\Omega)$
温湿循环 Moisture resistance	MIL-STD-202 METHOD 106	25°C~65°C,90% ~ 100%RH, 2.5 小时; 65°C 90% ~ 100%RH, 3 小时; 65°C~25°C,80% ~ 100%RH,2.5 小时 , 10 个循环 , 试验结束 24 \pm 4 小时后进行测试。 25°C~65°C,90% ~ 100%RH, 2.5H; 65°C 90% ~ 100%RH, 3H; 65°C~25°C 80% ~ 100%RH, 2.5H, 10 cycles, Measurement at 24 \pm 4 hours after test conclusion.	0.5%/1%: $\pm(1.0\%+0.05\Omega)$ 5%: $\pm(2.0\%+0.05\Omega)$
焊锡性 Solder ability	JIS C 5201 4.17	沾助焊剂后浸入锡炉, 锡炉温度 245 \pm 5°C, 时间 3 \pm 0.5 秒。 Dip the terminal in a flux and then dip into a soldering bath at 245 \pm 5°C for 3 \pm 0.5sec.	> 95%面积上锡 (>95% coverage)
抗焊锡热 Resist to soldering heat	JIS C 5201 4.18	沾助焊剂后浸入锡炉, 锡炉温度 260 \pm 5°C, 时间 10 \pm 0.5 秒, 测量试验前后的阻值变化率。 Dip the terminal in a flux and then dip into a soldering bath at 260 \pm 5°C for 10 \pm 0.5sec. Measure the variation of resistance.	$\pm(1.00\% + 0.05\Omega)$
绝缘电阻 Insulation resistance	JIS C 5201 4.6	电阻本体上加载绝缘耐压 60 \pm 5 秒后, 测量绝缘阻抗。 Applied the dielectric withstanding voltage on the center of body for 60 \pm 5seconds. Then measure insulation resistance.	>10G Ω

FTR 系列抗硫化车规薄膜片式电阻器规格书

内容 Item	测试方法 Test Methods	测试条件 Test Conditions	规格 Specification
绝缘耐压 Dielectric withstanding voltage	JIS C 5201 4.7	电阻本体上加载绝缘耐压 60±5 秒。 Applied the dielectric withstanding voltage on the center of body for 60±5 seconds.	无击穿、飞溅及可见机械性损伤 No evidence of flash over, mechanical damage arcing or insulation breakdown
温湿循环 Moisture resistance	MIL-STD-202 METHOD 106	25°C~65°C, 90%~100%RH, 2.5 小时; 65°C 90%~100%RH, 3 小时; 65°C~25°C, 80%~100%RH, 2.5 小时, 10 个循环, 试验结束 24±4 小时后进行测试。 25°C~65°C, 90%~100%RH, 2.5H; 65°C 90%~100%RH, 3H; 65°C~25°C 80%~100%RH, 2.5H, 10 cycles, Measurement at 24±4 hours after test conclusion.	0.5%/1%:±(1.0%+0.05Ω) 5%:±(2.0%+0.05Ω)
耐湿特性 Humidity	MIL-STD-202 METHOD 103 AEC-Q200 TEST 7	电阻放入恒温恒湿箱, 加载 10%额定功率, 85°C /85%RH, 持续通电 1000+24/-0H, 试验结束 24±4 小时后进行测试 Put the specimen in a chamber Load 10% of operating power, 1000 hours 85°C/85%RH. Measurement at 24±4 hours after test conclusion.	0.5%、1%:±(1.0%+0.05Ω) 5%:±(2.0%+0.05Ω)
负荷寿命 Load life	MIL-STD-202 METHOD 108 AEC-Q200 TEST 8	电阻放入恒温箱中, 温度 125±2°C, 加载 45%额定功率 ON TIME:1.5H, OFF TIME:0.5H, 通电 1000+24/-0H, 试验结束 24±4 小时后进行测试 Put the specimen in a chamber at 125±2°C temperature, Load 45% rated power ON TIME:1.5H, OFF TIME:0.5H, and applied for 1000+24/-0H. Measurement at 24±4 hours after test conclusion.	0.5%、1%:±(1.0%+0.05Ω) 5%:±(2.0%+0.05Ω)
耐溶剂性 Resistance to Solvents	AEC-Q200 TEST 12 MIL-STD 202 METHOD 215	注意: 添加水性洗涤化学品-OKEM Clean 或等效物。请勿使用违禁溶剂 Note: Add Aqueous wash chemical - OKEM Clean or equivalent. Do not use banned solvents.	标识无脱落、损伤 No Marking fall off and broken
抗硫化实验 Sulfuration test	ASTM-B-809-95	方法一: 温度 105°C, 湿热蒸硫粉试验 (加饱和硝酸钾) 1000hrs Method1: steam sulfur powder test (with saturated potassium nitrate) at 105°C with humidity and heat (1000hrs)	±(3.0%+0.05Ω)Max
端子弯曲 Terminal bending	AEC-Q200 TEST 21 AEC-Q200-005	电阻焊接在测试板上进行弯折, 弯折保持时间 20±1 秒, 1206 (含) 以下的尺寸弯曲 5+0.2/0 mm; 1206 以上的尺寸弯曲 2+0.2/0 mm; 量测试验前后阻值变化率 Specimen shall be mounted on test board, then bend the board and maintained for 20±1s. the distance of bending is 5+0.2/0 mm for resistors which size no larger than 1206 or 2+0.2/0 mm which size larger than 1206. Measure the variation of resistance.	±(1.00% +0.05Ω)

内容 Item	测试方法 Test Methods	测试条件 Test Conditions	规格 Specification
		<p>测试板 (test board) 压头 (jig)</p>	

■ 本体标识 (Marking on the Resistor's Body)

<p>1.公差±5%的产品，以三字码标示，前两位表示阻值的有效数字，最后一位表示 10 的乘幂 ±5% tolerance product: the marking is 3 digits, the first 2 digits are significant figures of resistance value and the 3rd one denotes the power number of 10, (10X)</p> <p>2.±0.5%, ±1%, ±2%的产品，以四字码标示，前三位表示阻值的有效数字，最后一位表示 10 的乘幂 ±0.5%, ±1%, ±2% tolerance product: the marking is 4 digits, the first 3 digits are significant figures of resistance value and the 4th one denotes the power number of 10, (10X)</p> <p>3.0603 ±1% E96 系列的标准阻值，因电阻本体太小，采用三位代码标识。 Standard E96 series values of 0603 ±1%: due to the small size of the resistor's body, use 3digits code to indicate the resistance value.</p>		<p>472=47×10²=4.7KΩ</p>
		<p>10Ω以下标示: 5R6=5.6Ω Below 10Ω: 5R6=5.6Ω</p>
		<p>4992=499×10²=49.9KΩ</p>
		<p>100Ω以下标示 6R81=6.81Ω Below 100Ω: 6R81=6.81Ω</p>

■ 0603±1% E96 系列电阻值代码 Standard E96 Series Resistance Value Code for 0603 ±1% Marking

代码 Code	阻值 Value										
01	100	17	147	33	215	49	316	65	464	81	681
02	102	18	150	34	221	50	324	66	475	82	698
03	105	19	154	35	226	51	332	67	487	83	715
04	107	20	158	36	232	52	340	68	499	84	732

FTR 系列抗硫化车规薄膜片式电阻器规格书

05	110	21	162	37	237	53	348	69	511	85	750
06	113	22	165	38	243	54	357	70	523	86	768
07	115	23	169	39	249	55	365	71	536	87	787
08	118	24	174	40	255	56	374	72	549	88	806
09	121	25	178	41	261	57	383	73	562	89	825
10	124	26	182	42	267	58	392	74	576	90	845
11	127	27	187	43	274	59	402	75	590	91	866
12	130	28	191	44	280	60	412	76	604	92	887
13	133	29	196	45	287	61	422	77	619	93	909
14	137	30	200	46	294	62	432	78	634	94	931
15	140	31	205	47	301	63	442	79	649	95	953
16	143	32	210	48	309	64	453	80	665	96	976

0603±1%标记的倍增码 Multiplier Code for 0603 ±1% Marking

代码 Code	Y	X	A	B	C	D	E	F
指数 Multiplier	10 ⁻²	10 ⁻¹	10 ⁰	10 ¹	10 ²	10 ³	10 ⁴	10 ⁵

阻值标示如下 (So the resistance value are marked as the following examples)



$$10D = 124 \times 10^3 = 124K\Omega$$



$$38Y = 243 \times 10^{-2} = 2.43\Omega$$

0603 ±1%的产品，在标准 E24 系列中，但不属于 E96 系列，标示与 5%的字码相同，但是在中间字码下加一条线 (Standard E24 and not belong to E96 series values of 0603 ±1%, the marking is the same as 5% tolerance but marking as underline)




$$3\bar{3}1 = 33 \times 10^1 = 330\Omega$$




$$5\bar{6}0 = 56 \times 10^0 = 56\Omega$$

焊接 (soldering)

- 建议回流焊曲线 (Recommend reflow soldering profile)



- 建议波峰焊曲线 (Recommend wave soldering profile)




- 手工焊温度 (hand soldering temperature)

烙铁温度 $350 \pm 10^{\circ}\text{C}$ 3 秒之内, 避免烙铁接触电阻本体

The iron temperature is $350 \pm 10^{\circ}\text{C}$, hand soldering time less than 3S. Avoid solder iron tip direct touch the components body

■ 包装规格 (Tapping Specification)

FTR-Series Automotive Anti-sulfured
Thin Film Chip Resistor Product Specifications
FTR 系列抗硫化车规薄膜片式电阻器规格书




Standard Quantity per Reel
5000 pcs/Reel

- 卷盘尺寸 (Reel dimension)

Type	Size	Unit	A	B	C	F	W
0402	7"	10K/Reel	mm 178±2.0	60.0±1.0	13.5±0.5	11.4±0.1	9.00±0.3
0402	13"	40K/50K Reel	mm 330±2.0	100.0±1.0	13.5±0.5	11.4±0.1	9.00±0.3
0603/0805/1206/1210	7"	5K/Reel	mm 178±2.0	60.0±1.0	13.5±0.5	11.4±0.1	9.00±0.3
0603/0805/1206	10"	10K/Reel	mm 254±2.0	100.0±1.0	13.5±0.5	11.4±0.1	9.00±0.3
0603/0805/1206	13"	20K/Reel	mm 330±2.0	100.0±1.0	13.5±0.5	11.4±0.1	9.00±0.3
1218/1812/2010/2512	7"	4K/Reel	mm 178±2.0	60.0±1.0	13.5±0.5	15.4±1.0	13.0±0.3

- 包装尺寸 (packing dimension)


纸带编带 Paper Taping



Unit: mm

Dim	A	B	D	F	P0	P1	P2	W	T
0402	0.65±0.10	1.15±0.10	1.50±0.10	3.50±0.05	4.00±0.10	2.00±0.10	2.00±0.05	8.00±0.20	0.42±0.03
0603	1.10±0.10	1.90±0.10	1.50±0.10	3.50±0.05	4.00±0.10	4.00±0.10	2.00±0.05	8.00±0.20	0.60±0.03
0805	1.65±0.20	2.40±0.20	1.50±0.10	3.50±0.05	4.00±0.10	4.00±0.10	2.00±0.05	8.00±0.20	0.75±0.05
1206	1.90±0.20	3.50±0.20	1.50±0.10	3.50±0.05	4.00±0.10	4.00±0.10	2.00±0.05	8.00±0.20	0.75±0.05
1210	2.80±0.20	3.50±0.20	1.50±0.10	3.50±0.05	4.00±0.10	4.00±0.10	2.00±0.05	8.00±0.20	0.75±0.05

塑料带编带 Embossed Taping




Unit: mm

Dim	B0	A0	D0	F	P0	P	P1	W	K0
1218	2.80±0.20	4.60±0.20	1.50±0.10	5.50±0.05	4.00±0.10	4.00±0.10	2.00±0.05	12.0±0.10	0.75±0.10
1812	3.52±0.10	5.10±0.10	1.50±0.10	5.50±0.05	4.00±0.10	4.00±0.10	2.00±0.05	12.0±0.10	0.78±0.10
2010	2.75±0.10	5.40±0.10	1.50±0.10	5.50±0.05	4.00±0.10	4.00±0.10	2.00±0.05	12.0±0.10	0.75±0.10
2512	3.35±0.10	6.70±0.10	1.50±0.10	5.50±0.05	4.00±0.10	4.00±0.10	2.00±0.05	12.0±0.10	0.75±0.10

上胶带剥离力测试 (Peel force of top cover tape)

上胶带以 200mm/分钟的速度，沿 165~180 度角的方向进行剥离，如下图所示。纸带的剥离力范围为 10g~70g；载带的剥离力范围 30~100g。

The top cover tape is pulled at a speed of 200 mm/min with the angle between the tape during peel and the direction of unreeling maintained at 165 to 180 degree as following picture. The peel force of paper carrier tape shall be 0.1N to 0.7N(10 to 70 g), the peel force of plastic carrier tape shall be 0.3N to 1N (30 to 100 g)



■ 薄膜电阻器使用说明 (Chip Resistor Instructions for use)

本产品以下特殊环境下应用，性能可能会受到影响：

(Application of the products in a special environment can deteriorate product performance):

1. 高温；
High temperature
2. 有海风或腐蚀性气体，包括氯气，硫化氢，氨气，二氧化硫，二氧化氮等；
Near the sea ,or corrosive gas, such as Cl_2 , H_2S , NH_3 , SO_2 , and NO_2 , etc;
3. 各种类型的液体，包括水，油，化学品，有机溶剂的使用；
Unverified liquids, such as water, oil, chemical or organic solvent;
4. 在用树脂或其他涂层材料密封产品的情况下使用；
Unverified resin or paint to cover products;
5. 焊接后使用不洁焊剂或使用水或水溶性清洁剂清洗产品
Products should be washed with soluble cleaner even if non cleaning flux.

- 储存 / 搬运条件 (Storage / Carry conditions)

1. 储存温度 $25\pm 5^{\circ}C$ Temperature: $25\pm 5^{\circ}C$
2. 湿度 30%~70%RH Humidity: 30%~70%RH
3. 储存期限: 先进先出, 2年 Storage life: 2years FIFO
4. 存放和搬运时，请保持盒子的正确方向。严禁跌落在箱体上，否则可能损坏产品电极或本体
Please hold box correct orientation when storing and carrying. It is strictly prohibited to fall on the box.
otherwise the product electrode or body may be damaged.

